


GEORGIA CORRECTIONAL INDUSTRIES: POWDERED GREASE SOLVENT

SAFETY DATA SHEET

SECTION 1 – PRODUCT NAME AND COMPANY IDENTIFICATION

- 1.1 Product name: Heavy Duty Grease Solvent
General use: Proprietary industrial cleaner
Product description: White granular powder
Product number(s): 07327
- 1.2 Manufacturer: Georgia Correctional Industries, 2984 Clifton Springs, Rd., Decatur, GA 30034
Telephone number: (800) - 252 - 7130, (404) - 244 - 5100
Emergency number: Chemtrec: (800) - 424 - 9300
Date prepared: Feb. 24, 2015; supersedes any previous editions

SECTION 2 – HAZARDS IDENTIFICATION

- 2.1 Classification of the substance: Cat. 1C, Skin Cat. 1, Eye  GHS05
- 2.2 Signal word: **DANGER**
- 2.3 Hazard statement: H314: Causes severe skin burns and eye damage.
- 2.4 Precautionary prevention statements: P260: Do not breathe dust / fume / gas / mist / vapors / spray.
P260: Wash exposed skin thoroughly after handling.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
- 2.5 Precautionary response statements: P312: **Immediately** call a POISON CENTER or doctor/physician if you feel unwell.
P301, P330, P381: **IF SWALLOWED:** Rinse mouth. Do NOT induce vomiting.
P304, P340: **IF INHALED:** Remove victim to fresh air, rest in a position comfortable for breathing.
P305, P351, P338: **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing as needed.
P363: Wash contaminated clothing before reuse.
- 2.6 Precautionary storage statement: P405: Store locked up.
- 2.7 Precautionary disposal statement: P501: Dispose of contents/container in accordance with local/regional/national/international regulations.
- 2.7 NFPA / HMIS rating: 2, 0, 0, COR

SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS

3.1 Hazardous components:	CAS #	% by wt.	OSHA PEL		ACGIH TLV		SARA TITLE III	RQ (lbs.)
			PPM	mg/M ³	PPM	mg/M ³		
Sodium carbonate	497-19-8	< 30%	Not est.		Not est.		311 / 312	ND
Silicic acid disodium salt	6834-92-0	< 30%	2	2	Not est.		311 / 312	ND
Sodium tripolyphosphate	7758-29-4	< 20%	Not est.		Not est.		311 / 312	5000

The remaining components of this product are non-hazardous or are in small enough quantities as to not meet regulatory thresholds for disclosure. These components contain no substances or impurities which would influence the classification of this product. All components and their specific proportions in this product are considered proprietary to Georgia Correctional Industries.

SECTION 4 – FIRST AID MEASURES

- 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product. Always seek medical help for any exposure.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
Supply fresh air. If required, provide artificial respiration. Keep patient warm.
- After skin contact: Immediately rinse with water. Seek immediate medical advice.
- After eye contact: Remove contact lenses if worn. Rinse eye for several minutes under running water. Seek medical advice.
- After swallowing: Do not induce vomiting; call for medical help immediately. Rinse out mouth and then drink plenty of water.
A person vomiting while on their back should be turned onto their side.

SECTION 5 – FIRE FIGHTING PROCEDURES

- 5.1 Extinguishing media: Carbon dioxide, water fog, chemical foam, dry chemical. Material is non-flammable.
- 5.2 General hazards: Material is irritating, avoid contact and conditions that result in agitating or foaming the material.
- 5.3 Advice for firefighters: Protective equipment: Wear a self-contained respiratory protective device.
- 5.4 Unusual hazards: None.
- 5.5 Firefighting procedures: Keep containers cool with water spray to prevent container rupture due to steam buildup; floor will become slippery if material is released. Material is alkaline and will irritate the eyes if product or fumes contact the eyes.
- 5.6 Decomposition compounds: Oxides of carbon, sodium, sulfur, phosphorus, and silicon may be released with sufficient thermal energy.

GEORGIA CORRECTIONAL INDUSTRIES: POWDERED GREASE SOLVENT

SECTION 6 – ACCIDENTAL RELEASE MEASURES

- 6.1 Protective equipment and emergency procedures: Wear protective equipment. Keep unprotected persons away. Particular danger of slipping on leaked/spilled product. ensure adequate ventilation, material is irritating, avoid direct contact.
- 6.2 Environmental precautions: Dilute with plenty of water and do not allow it to enter sewers, surface or ground water.
- 6.3 Methods and materials for containment and clean up: Use dustless methods (vacuum) to remove spills and place in disposable container. Do not dry sweep and use face masks with respirators when dust cannot be controlled. Wet spilled product to control dust and contain with adsorbent materials. Clean the affected area carefully, dispose contaminated material as waste according to Section 13.
- 6.4 Reference to other sections: See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment.

SECTION 7 – HANDLING AND STORAGE

- 7.1 Precautions for safe handling: Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols and dusts.
- 7.2 Conditions for safe storage: Do not store together with acids or foodstuffs. Store in cool, dry conditions in well sealed receptacles.
- 7.3 Specific end use(s): No further relevant information available.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

- 8.1 Exposure controls:
- General protective and hygienic measures:** Keep away from foodstuffs and beverages. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid direct contact with the eyes and skin. Only handle material in a well ventilated area and avoid dust formation.
- Respiratory protection:** None required unless product is aerated, dusted or sprayed.
- Protection of hands:** Protective gloves, the glove material has to be impermeable and resistant to the product, such as neoprene, butyl or nitrile rubber gloves with cuffs.
- Eye protection:** Safety glasses and / or goggles with side shields.
- Body protection:** Protective work clothing.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

- 9.1
- | | |
|---|-----------------------|
| Appearance: | White granular powder |
| Odor: | Bland |
| Odor threshold: | ND |
| pH: | 12.0 - 12.5 |
| Melting point / freezing point: | ND |
| Initial boiling point and boiling range: | ND |
| Flash point: | ND |
| Evaporation rate: | ND |
| Flammability (solid, gas): | ND |
| Upper / lower flammability or explosive limits: | ND |
| Vapor pressure: | ND |
| Vapor density: | ND |
| Relative density: | 2.3 - 2.5, 25°C |
| Solubility: | Soluble in water |
| Partition coefficient: n-octanol/water: | ND |
| Autoignition temperature: | ND |
| Decomposition temperature: | ND |
- 9.2 Other information: None

SECTION 10 –STABILITY AND REACTIVITY

- 10.1 Reactivity: No spontaneous reactivity
- 10.2 Chemical stability: Thermal decomposition possible at temperatures exceeding 600°F, no decomposition if used according to specifications.
- 10.3 Possible hazardous reactions: Corrosive action on metals, reacts with powdered metals, reacts strongly with acids.
- 10.4 Conditions to avoid: No further relevant information available.
- 10.5 Incompatible materials: Strong oxidizers and acids.
- 10.6 Decomposition products: Oxides of carbon, phosphorus, silicon, sulfur and sodium.

GEORGIA CORRECTIONAL INDUSTRIES: POWDERED GREASE SOLVENT

SECTION 11 – TOXICOLOGICAL INFORMATION

11.1	Hazardous Ingredients	CAS #	EINECS #	LD 50, species / route
	Sodium carbonate	497-19-8	207-838-8	LD50, Rat, oral, 4090 mg/kg
	Silicic acid disodium salt	6834-92-0	229-912-9	LD50, Rat, oral, 800 mg/kg
	Sodium tripolyphosphate	7758-29-4	231-838-7	LD50, Rat, oral, 6500 mg/kg
11.2	Serious eye damage/irritation:	Causes severe eye damage.		
11.3	Respiratory or skin sensitization:	No data available		
11.4	Repeated dose toxicity:	No data available		
11.5	STOT (single/repeated)	No data available		
11.6	Carcinogenicity:	No data available		
11.7	Mutagenicity:	No data available		
11.8	Reproductive toxicity:	No data available		

SECTION 12 – ECOLOGICAL INFORMATION

12.1	Toxicity:	Sodium carbonate:	LC50, Fathead minnow, 320 mg / liter (96 hours)
		Silicic acid disodium salt:	LC50, Fathead minnow, 500 mg / liter (96 hours)
		Sodium tripolyphosphate:	LC50, Fathead minnow, 100 mg / liter (96 hours)
		Finished product:	No available data.
12.2	Persistence and degradability:	Expected to be easily biodegradable based on composition.	
12.3	Bioaccumulative potential:	Not expected to exhibit this behavior based on composition.	
12.4	Soil mobility:	No specific data available.	
12.5	General information:	No data are available on the adverse effects of this material on the environment. Neither COD nor BOD data are available. Based on the chemical composition of this product it is assumed that the mixture can be treated in an acclimatized biological waste treatment plant system in limited quantities. However, such treatment should be evaluated and approved for each specific biological system. None of the ingredients in this mixture are classified as a Marine Pollutant.	

SECTION 13 – DISPOSAL CONSIDERATIONS

13.1	Waste treatment methods:	It is recommended that small amounts may be diluted with plenty of water and washed away. Dispose of bigger amounts in accordance with Local Authority requirements. Refer to 40 CFR 260 - 299 for complete waste disposal regulations for alkaline materials. Consult your local, state, or federal agency before disposing of any chemicals.
------	--------------------------	--

SECTION 14 – TRANSPORTATION INFORMATION

14.1	UN number:	UN3262
	DOT, ADR, IMDG, IATA	
14.2	Proper shipping name:	Corrosive solid, basic, inorganic, n.o.s.
	DOT, ADR, IMDG, IATA	
14.3	Transport hazard class:	8
	DOT, ADR, IMDG, IATA	
14.4	Packing group:	III, corrosive
	DOT, ADR, IMDG, IATA	
14.5	Environmental hazards:	None
	Marine	

Note: Transportation information provided is for reference only. Customer is urged to consult 49 CFR 100 - 177, IMDG, IATA, EC, United Nations TDG, and WHMIS (Canada) TDG information manuals for detailed regulations and exceptions covering specific container sizes, packaging materials and methods of shipping.

SECTION 15 – REGULATORY INFORMATION

15.1	TSCA:	All components of this product are listed on the U.S. Toxic Substances Control Act Chemical Inventory (TSCA Inventory) or are exempted from listing because a Low Volume Exemption has been granted in accordance with 40 CFR 723.50.
15.2	SARA TITLE III:	Not regulated under 302, 303, 313. Regulated under 311 / 312.
15.3	CERCLA:	Sodium tripolyphosphate CAS # 7758-29-4 RQ 5000lbs.
15.4	Clean Air Act:	No ingredients defined as Hazardous Air Pollutants or Stratospheric Ozone Depleting.
15.5	California Prop. 65:	Not listed.
15.6	Right To Know	NJ, PA, MA. Not listed.
15.7	CPR classification:	WHMIS Classification: E, D2
15.8	Canadian IDL:	Components of this product identified by CAS number and listed on the Canadian Ingredient Disclosure List are shown in Section 2.
15.9	Can. DSL / NDSL:	Components of this product identified by CAS number are listed on the DSL or NDSL, or are otherwise in compliance with the New Substances Notification (NSN) regulations. Only ingredients classified as "hazardous" are listed in Section 2 unless otherwise indicated.
15.10	EINECS:	Components of this product identified by CAS numbers are on the European Inventory of Existing Commercial Chemical Substances.

GEORGIA CORRECTIONAL INDUSTRIES: POWDERED GREASE SOLVENT

SECTION 16 – OTHER INFORMATION

16.1 Risk phrases: R35 / 41: Causes serious skin burns / Risk of serious damage to eyes.
Safety phrases: S36 / 37 / 39: Wear protective clothing, gloves, and eye / face protection.



Symbol for label:

The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. Users are advised to confirm in advance of need that information is current, applicable and suited to the circumstances of use. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, vendor assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed. Any questions regarding this product should be directed to the manufacturer of the product as described in Section 1.