

Georgia Correctional Industries
TECHNICAL PRODUCT DATA SHEET

HOLD-UP FLOOR FINISH

PRODUCT NUMBERS:

4/1 Gal. Case	07800
5 Gal. Pail	07801
55 Gal. Drum	07802
5 Gal. Bag/Box	07804

GENERAL DESCRIPTION:

GCI Hold-Up Floor Finish is an exceptional metal interlock floor finish that provides the maximum combination of gloss and durability and a minimum of maintenance. Hold-Up dries to a deep, even shine with a brilliant wet look luster that withstands wear. Special metal cross-link co-polymers provide exceptional resistance to black heel markings, scuffs, powdering, detergent solutions, spills, and water spotting. Spray buffing brightens the gloss, hardens the film, and removes any heel marks and other soils. Hold-Up meets or exceeds all standards for slip resistance. Hold-Up won't yellow even long after application. Hold-Up adds a hard, clear finish to all resilient floor surfaces such as vinyl composition, rubber, linoleum, terrazzo, and builds a strong base for prolonged wear.

PHYSICAL PROPERTIES:

Appearance & Odor:	White emulsion liquid with an acrylic odor.
Specific Gravity:	1.025 – 1.035
pH (undiluted):	8.0 – 9.0
Solubility in Water:	Dispersible
Volatile by Weight:	70 – 80

DIRECTIONS FOR USE:

Request a copy of the "GCI Procedure for Stripping and Waxing Floors."

(1) Thoroughly strip floor using a GCI Floor Stripper. Floor must be completely stripped of all old wax build-up. (2) Rinse floor with clean water being sure to totally neutralize and remove any residual stripper. (3) After thorough rinse, lightly buff floor with a fine pad. (4) Being sure floor is clean and dry, apply two coats of GCI Enduro-Seal or Hold-up as a sealer base as recommended for worn and high traffic areas. (5) Using clean cotton mops, apply two or more coats of the Hold-Up finish. Coats should be thin, not heavy. Apply with light, even strokes across floor without scrubbing action. Allow a minimum of 30 minutes drying time between coats, longer in damp, humid weather. Be sure one coat is completely dry before applying another. Do not attempt to retouch or repair miss spots until dry.

MAINTANENCE:

(1) Sweep as required. (2) Damp mop or scrub lightly with GCI Neutral Floor Cleaner as recommended. (3) Use GCI Two-In-One Spray Buff/Maintainer and buff as directed.

STORAGE AND DISPOSAL:

Keep from freezing. Store in a cool dry area. Avoid excessive heat. Flush with plenty of water to the sanitary sewer. Dispose of in accordance with local, State, and Federal regulations.

PRODUCT SAFETY:

This product can cause irritation to the eyes and skin. Do not take internally. May cause abdominal discomfort. Avoid prolonged contact with eyes, skin, and clothing. Upon contact with skin or flush with water. KEEP OUT OF REACH OF CHILDREN. Read and understand the provided GCI Hold-Up Floor Finish MSDS for first aid and other safety information.

Revision 1