

GEORGIA CORRECTIONAL INDUSTRIES

Administrative Offices 2984 Clifton Springs Road • Decatur, Georgia 30034 404-244-5100 • 800-282-7130 • Fax 404-244-5141

Norman E. Wilson Executive Director

TECHNICAL PRODUCT DATA SHEET

SHINE-ON FLOOR FINISH

PRODUCT NUMBERS:

| 4/1 Gal. Case | 07810 |
|----------------|-------|
| 5 Gal. Pail | 07811 |
| 55 Gal. Drum | 07812 |
| 5 Gal. Bag/Box | 07814 |

GENERAL DESCRIPTION:

GCI Shine-On Floor Finish is an exceptional acrylic copolymer floor finish that provides the maximum combination of gloss and durability. Shine-On dries to a deep, even shine with a brilliant wet look luster that withstands wear. Shine-On is specially formulated to provide best results with either high speed or low speed buffing equipment and contains 18% solids which makes for easy use. This floor finish resists black heel marking, scuffs, scratches, powdering, detergents, spills, and water spotting. Shine-On meets or exceeds all standards for slip resistance. Shine-On is suitable for use on all resilient floor surfaces such as vinyl composition, rubber, linoleum, and terrazzo.

PHYSICAL PROPERTIES:

| Appearance & Odor: | White emulsion liquid with an acrylic odor. |
|----------------------|---|
| Specific Gravity: | 1.02 - 1.03 |
| pH (undiluted): | 8.0 - 9.0 |
| Solubility in Water: | Dispersible |
| Volatile by Weight: | 70 - 80 |

DIRECTIONS FOR USE:

(1) Thoroughly strip floor using a GCI Floor Stripper. Floor must be completely stripped of all old wax build-up. (2) Rinse floor with clean water being sure to totally neutralize and remove any residual stripper. (3) After thorough rinse, lightly buff floor with a fine pad. (4) Being sure floor is clean and dry, apply two coats of GCI Enduro-Seal or Shine-On as a sealer base as recommended for worn and high traffic areas. (5) Using clean cotton mops, apply two or more coats of the Shine-On finish. Coats should be thin, not heavy. Apply with light, even strokes across floor without scrubbing action. Allow a minimum of 30 minutes drying time between coats, longer in damp, humid weather. Be sure one coat is completely dry before applying

another. Do not attempt to retouch or repair miss spots until dry.

MAINTANENCE:

(1) Sweep as required. (2) Damp mop or scrub lightly with GCI Neutral Floor Cleaner as recommended. (3) Use GCI Two-In-One Spray Buff/Maintainer and buff as directed.

STORAGE AND DISPOSAL:

Keep from freezing. Store in a cool dry area. Avoid excessive heat. Flush with plenty of water to the sanitary sewer. Dispose of in accordance with local, State, and Federal regulations.

PRODUCT SAFETY:

This product can cause irritation to the eyes and skin. Do not take internally. May cause abdominal discomfort. Avoid prolonged contact with eyes, skin, and clothing. Upon contact with skin or flush with water. Keep out of reach of children. Read the Shine-On MSDS for addition information.